


LGMG Electric - Articulating Boom Lift


SPECIFICATIONS


Measurements Metric US Work Height Max. 11m 36'1" Platform Height 9m 29'6" Horizontal Outreach 6.25m 20'6" Up and Over Height 4.12m 13'6" Platform Length 1.17m 3'10" Platform Length 1.17m 3'10" Platform Width 0.76m 2'6" Platform Capacity 230kg 507 lbs Stowed Length 5.46m 17'11" © Overall Width 1.19m 3'11" © Stowed Height 2m 6'7" © Wheelbase 1.58m 5'2" © Ground Clearance 0.09m 4" Productivity Max. Platform Occupants 2(in) / 2(out) Turntable Rotation 355° 355° Drive Speed-Stowed 5km/h 3.1mph Drive Speed-Raised 0.65km/h 0.4mph Gradeability 30% 30% Max. Wind Speed 1.65m 5'5" Turning Radius	Models	A09JE ((A30JE)
Platform Height 9m 29'6" Horizontal Outreach 6.25m 20'6" Up and Over Height 4.12m 13'6" Platform Length 1.17m 3'10" Platform Width 0.76m 2'6" Platform Capacity 230kg 507 lbs Stowed Length 5.46m 17'11" Overall Width 1.19m 3'11" Stowed Height 2m 6'7" Wheelbase 1.58m 5'2" Ground Clearance 0.09m 4" Productivity Max. Platform Occupants 2(in) / 2(out) Turntable Rotation 355° 355° Drive Speed-Stowed 5km/h 3.1mph Drive Speed-Raised 0.65km/h 0.4mph Gradeability 30% 30% Max. Wind Speed 12.5m/s 28mph Turning Radius-Inside 1.65m 5'5" Turning Radius-Outside 3.15m 10'4" Max.Slope 2.5°/4.5° 2.5°/4.5° <td< td=""><td>Measurements</td><td>Metric</td><td>US</td></td<>	Measurements	Metric	US
Horizontal Outreach Up and Over Height Horizontal Outreach Up and Over Height Hatform Length 1.17m 3'10" Platform Length 1.17m 3'10" Platform Width 0.76m 2'6" Platform Capacity 230kg 507 lbs Stowed Length 5.46m 17'11" Overall Width 1.19m 3'11" Stowed Height 2m 6'7" Wheelbase 1.58m 5'2" Ground Clearance 0.09m 4" Productivity Max. Platform Occupants 2(in) / 2(out) Turntable Rotation 355° 355° Drive Speed-Stowed 5km/h 3.1mph Drive Speed-Raised 0.65km/h 0.4mph Gradeability 30% 30% Max. Wind Speed 1.65m 5'5" Turning Radius-Inside 1.65m 5'5" Turning Radius-Outside 3.15m 10'4" Max.Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power Power Source 48V AC 390Ah Hydraulic System Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Work Height Max.	11m	36'1"
Up and Over Height	Platform Height	9m	29'6"
Platform Length 1.17m 3'10" Platform Width 0.76m 2'6" Platform Capacity 230kg 507 lbs Stowed Length 5.46m 17'11" Overall Width 1.19m 3'11" Stowed Height 2m 6'7" Wheelbase 1.58m 5'2" Ground Clearance 0.09m 4" Productivity Max. Platform Occupants 2(in) / 2(out) Turntable Rotation 355° 355° Drive Speed-Stowed 5km/h 3.1mph Drive Speed-Raised 0.65km/h 0.4mph Gradeability 30% 30% Max. Wind Speed 12.5m/s 28mph Turning Radius-Inside 1.65m 5'5" Turning Radius-Outside 3.15m 10'4" Max.Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power 48V AC 390Ah	Horizontal Outreach	6.25m 20'6"	
Platform Width 0.76m 2'6" Platform Capacity 230kg 507 lbs Stowed Length 5.46m 17'11" Overall Width 1.19m 3'11" Stowed Height 2m 6'7" Wheelbase 1.58m 5'2" Ground Clearance 0.09m 4" Productivity Max. Platform Occupants 2(in) / 2(out) Turntable Rotation 355° 355° Drive Speed-Stowed 5km/h 3.1mph Drive Speed-Raised 0.65km/h 0.4mph Gradeability 30% 30% Max. Wind Speed 12.5m/s 28mph Turning Radius-Inside 1.65m 5'5" Turning Radius-Outside 3.15m 10'4" Max. Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power 48V AC 390Ah Hydraulic System 17L 4.5gal	Up and Over Height	4.12m	13'6"
Platform Capacity 230kg 507 lbs Stowed Length 5.46m 17'11" Overall Width 1.19m 3'11" Stowed Height 2m 6'7" Wheelbase 1.58m 5'2" Ground Clearance 0.09m 4" Productivity Max. Platform Occupants 2(in) / 2(out) Turntable Rotation 355° 355° Drive Speed-Stowed 5km/h 3.1mph Drive Speed-Raised 0.65km/h 0.4mph Gradeability 30% 30% Max. Wind Speed 12.5m/s 28mph Turning Radius-Inside 1.65m 5'5" Turning Radius-Outside 3.15m 10'4" Max.Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Platform Length	1.17m	3'10"
Stowed Length 5.46m 17'11" ⑤ Overall Width 1.19m 3'11" ⑥ Stowed Height 2m 6'7" ⑥ Wheelbase 1.58m 5'2" ⑥ Ground Clearance 0.09m 4" Productivity Max. Platform Occupants 2(in) / 2(out) Turntable Rotation 355° 355° Drive Speed-Stowed 5km/h 3.1mph Drive Speed-Raised 0.65km/h 0.4mph Gradeability 30% 30% Max. Wind Speed 12.5m/s 28mph Turning Radius-Inside 1.65m 5'5" Turning Radius-Outside 3.15m 10'4" Max.Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Platform Width	0.76m	2'6"
③ Overall Width 1.19m 3'11" ⑤ Stowed Height 2m 6'7" ⑥ Wheelbase 1.58m 5'2" ③ Ground Clearance 0.09m 4" Productivity Max. Platform Occupants 2(in) / 2(out) Turntable Rotation 355° 355° Drive Speed-Stowed 5km/h 3.1mph Drive Speed-Raised 0.65km/h 0.4mph Gradeability 30% 30% Max. Wind Speed 12.5m/s 28mph Turning Radius-Inside 1.65m 5'5" Turning Radius-Outside 3.15m 10'4" Max.Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Platform Capacity	230kg	507 lbs
● Stowed Height 2m 6'7" ● Wheelbase 1.58m 5'2" ● Ground Clearance 0.09m 4" Productivity Max. Platform Occupants 2(in) / 2(out) Turntable Rotation 355° 355° Drive Speed-Stowed 5km/h 3.1mph Drive Speed-Raised 0.65km/h 0.4mph Gradeability 30% 30% Max. Wind Speed 12.5m/s 28mph Turning Radius-Inside 1.65m 5'5" Turning Radius-Outside 3.15m 10'4" Max. Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Stowed Length	5.46m	17'11"
● Wheelbase 1.58m 5'2" ● Ground Clearance 0.09m 4" Productivity Max. Platform Occupants 2(in) / 2(out) Turntable Rotation 355° 355° Drive Speed-Stowed 5km/h 3.1mph Drive Speed-Raised 0.65km/h 0.4mph Gradeability 30% 30% Max. Wind Speed 12.5m/s 28mph Turning Radius-Inside 1.65m 5'5" Turning Radius-Outside 3.15m 10'4" Max. Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Overall Width	1.19m	3'11''
Ground Clearance 0.09m 4" Productivity Max. Platform Occupants 2(in) / 2(out) Turntable Rotation 355° 555° Drive Speed-Stowed 5km/h 3.1mph Drive Speed-Raised 0.65km/h 0.4mph Gradeability 30% 30% Max. Wind Speed 12.5m/s 28mph Turning Radius-Inside 1.65m 5'5" Turning Radius-Outside 3.15m 10'4" Max.Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Stowed Height	2m	6'7"
Productivity Max. Platform Occupants 2(in) / 2(out) Turntable Rotation 355° 355° Drive Speed-Stowed 5km/h 3.1mph Drive Speed-Raised 0.65km/h 0.4mph Gradeability 30% 30% Max. Wind Speed 12.5m/s 28mph Turning Radius-Inside 1.65m 5'5" Turning Radius-Outside 3.15m 10'4" Max. Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Wheelbase	1.58m	5'2"
Max. Platform Occupants 2(in) / 2(out) Turntable Rotation 355° 355° Drive Speed-Stowed 5km/h 3.1mph Drive Speed-Raised 0.65km/h 0.4mph Gradeability 30% 30% Max. Wind Speed 12.5m/s 28mph Turning Radius-Inside 1.65m 5'5" Turning Radius-Outside 3.15m 10'4" Max.Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Ground Clearance	0.09m	4''
Turntable Rotation 355° 355° Drive Speed-Stowed 5km/h 3.1mph Drive Speed-Raised 0.65km/h 0.4mph Gradeability 30% 30% Max. Wind Speed 12.5m/s 28mph Turning Radius-Inside 1.65m 5'5" Turning Radius-Outside 3.15m 10'4" Max.Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Productivity		
Drive Speed-Stowed 5km/h 3.1mph Drive Speed-Raised 0.65km/h 0.4mph Gradeability 30% 30% Max. Wind Speed 12.5m/s 28mph Turning Radius-Inside 1.65m 5'5" Turning Radius-Outside 3.15m 10'4" Max.Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Max. Platform Occupants	2(in) / 2(out)	
Drive Speed-Raised 0.65km/h 0.4mph Gradeability 30% 30% Max. Wind Speed 12.5m/s 28mph Turning Radius-Inside 1.65m 5'5" Turning Radius-Outside 3.15m 10'4" Max.Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Turntable Rotation	355°	355°
Gradeability 30% 30% Max. Wind Speed 12.5m/s 28mph Turning Radius-Inside 1.65m 5'5" Turning Radius-Outside 3.15m 10'4" Max.Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Drive Speed-Stowed	5km/h	3.1mph
Max. Wind Speed 12.5m/s 28mph Turning Radius-Inside 1.65m 5'5" Turning Radius-Outside 3.15m 10'4" Max.Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Drive Speed-Raised	0.65km/h	0.4mph
Turning Radius-Inside 1.65m 5'5" Turning Radius-Outside 3.15m 10'4" Max.Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1"10"x7" Power Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Gradeability	30%	30%
Turning Radius-Outside 3.15m 10'4" Max.Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Max. Wind Speed	12.5m/s	28mph
Max.Slope 2.5°/4.5° 2.5°/4.5° Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Turning Radius-Inside	1.65m	5'5"
Tires Type Solid Non-marking Tires Size 557x178mm 1'10"x7" Power Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Turning Radius-Outside	3.15m	10'4''
Tires Size 557x178mm 1'10"x7" Power Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Max.Slope	2.5°/4.5°	2.5°/4.5°
Power Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Tires Type	Solid Non-marking	
Power Source 48V AC 390Ah Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Tires Size	557x178mm	1'10''x7''
Hydraulic System Hydraulic Oil Volume 17L 4.5gal	Power		
Hydraulic Oil Volume 17L 4.5gal	Power Source	48V AC 390Ah	
,	Hydraulic System		
Weight	Hydraulic Oil Volume	17L	4.5gal
weight	Weight		
Machine Weight (CE/ANSI) 6700kg 14770 lbs	Machine Weight (CE/ANSI)	6700kg	14770 lbs


STANDARD FEATURES		
Proportional control	Emergency descent	
Horn	Solid non-marking tires	
AC drive motor	Over tilt protection system	
AC lifting motor	Intelligent diagnostic system	
GPS connector	Overload sensing system	
Power switch	Auto-leveling platform	
Drop bar entry	Anti-entrapment protection	

OPTIONAL			
AC power to platform	Platform work light	Telematics	
Platform tool box	Platform swing gate	Toloillatios	









Please contact LGMG or a local dealer for more details.

LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only. This brochure comes into effect in September, 2022.

LINGONG HEAVY MACHINERY CO., LTD.

Address: No. 2676, Kejia Road, Jinan, Shandong, China Email: sales@lgmg.com.cn Tel:+86 531 6787 9283

LGMG Europe B.V.

Address: Laanweg 16 3208LC Spijkenisse Rotterdam, The Netherlands Email: sales@lgmgeurope.com Tel:+31 850 642 777

LGMG North America Inc.

Address: 1445 Sheffler Dr, Chambersburg, PA. 17201,USA Email: sales@lgmgna.com Tel:+1 833 288 5464

