BIBI

26-BL-W





BIBI

26-BL-W

The unique and award winning BIBI 26BL was the first unit in the revo-lutionary line of bi-leveling compact tracked based scissor lifts. With its ability to both travel and set up on uneven surfaces, adjusting to both front and rear as well as side sloping, the BIBI 26BL created a new lift category.

Its unique features allow the BIBI 26BL to get into work applications that no other lift can do thanks to its compact size, and replaces the use of much bigger units or alternative, less safe methods of access.

The BIBI 26BL is the new benchmark for efficient, safe access in uneven terrain.

	Technical data	Bibi 26 BL-W
Ī	Basket capacity	550lbs (2 op.)
	Max working height	25ft 11 in
	Max height basket floor	19ft 4in
	Moving height	16ft
	Lateral leveling for moving at heights	+/- 4°
	Powered	Gasoline Honda iGX390
	Powered (option)	Diesel Hatz 1B40
	Powered (option)	-
	Accelerator	Automatic
	Undercarriage	Bi-Leveling
	Basket leveling	Automatic
	Leveling Front	+/- 16°
	Leveling Rear	+/- 20°
	Side leveling	+/- 15°
	Power generator (option)	220V-1kW
	Electric pump (option)	220V-2kW
ľ	Hydraulic commands	Proportional
	Direction-Control System	Yes
	Easy-Drive System	Yes
	Kit for high speed	max 1.7 mph
	Ground emergency	Yes
	Control of inclination	Automatic
	Gradeability	25°
	Side slope	21°
	Length	6ft 5 in
1	Width	4ft 4in - 4ft 11in
	Min. machine height with folded railings	6ft 5in
	Total weight	5423 lbs
	Compliance	EN 280, ANSI, CSA, ASNZS1418



- Bi-leveling tracks (front, rear & side)
- 26ft work height
- 16ft drive height
- Auto leveling
- Honda engine
- Inclination control system
- Expandable basket







